

DOUBLE SLIDING DOOR

The double sliding door can be built from our mesh, polycarbonate, or steel sheet panels to fit your chosen machine guard system. Use the standard panel height 2,050 mm in up to 6 widths. You can also combine the standard panels or order special width panels to create the required door blade size.

The sliding doors are supplied with posts, panels, and door kit for assembly on site.

The door is built with an aluminum rail at the top where the runners move the door blade panels inside a single track. A guide rail at the bottom keeps the door blades in their position, making the sliding door very stable.

Depending on the risk assessment, you choose the preferred lock for your door; magnetic, Euro cylinder, Safe Lock or any other type of handle solution with or without a safety switch included.


The standard opening width is approximately 1,400-3,000 mm.




FACTS

ART. NO	COMPONENTS
36905530	Kit 5530 Double Sliding without lock
36908280	Kit 8280 Dbl Sliding door80x80


ACCESSORIES




SAFE LOCK PLD



SAFE LOCK PLE



SAFE LOCK PLD GL



SAFE LOCK PLE GL



EURO CYLINDER
LOCK


COMBINE WITH



POST 60X40



POST 80X80



PANEL ST30



PANEL FULL STEEL



DOUBLE SLIDING DOOR

MACHINE GUARD

IMAGES

