



TEST REPORT - Safe Lock

Smart Fix Door, 1600 Joules

Report No. TR-17-004A
Date: 2017-02-02
Place: Troax Test Center



TEST MATERIAL

Panel: ST30 2050x800 mm
Post: 60x40x2200 mm
Fixing: Smart Fix hinge
Door lock: Safe Lock
Floor fixing: Bolted to test rig

PURPOSE

To document the effect of a high energy impact test from inside the hazard zone with Smart Fix machine guard door equipped with a Safe Lock (without switch).

TEST PROCEDURE

Pendulum mass: 100 kg
Pendulum speed: 20 km/h
Impact energy: 1600J

The test was performed in accordance with the pendulum test method stated in ISO14120:2015 Annex C. Door blade, Safe Lock, panels and posts were assembled with the Smart Fix system according to the assembly instruction and then fixed to the test rig with M10 bolts. The pendulum was adjusted so the impact hits the panel 1466mm above the floor, 2/3 of the total wall height of 2200 mm. To reach the energy of 1600 J the pendulum was raised 1629 mm from the starting point.

RESULTS

The Smart Fix door with the Safe Lock withstand the high energy impact. The door panel and the posts absorb all energy and obtain a remaining deformation. The deflection of the door panel was approximately 300 mm in the upper corner. Despite the high energy impact there was no penetration and no parts departed.



Address
Troax AB
Box 89
SE-335 04 Hillerstorp
Sweden

Telephone
+46 (0)370 828 00

Reg.No.
556093-5719

Website
www.troax.com
E-mail
info@troax.com