


GOLF

The TÜV-tested and flexible d-flexx Rack-End Barriers Golf protect the rack ends in outdoor and indoor use. Once installed, the rack end is not in direct contact with the rack to be protected. This allows the rack end protection to absorb the impact energy. Cost and time consuming maintenance work will be reduced to the minimum. The moveable cuffs additionally absorb the impact energy. The double rack end is for driveways with heavy pallet trucks. The fixing material is always included in the delivery of d-flexx-Rack-End Barriers Golf. The fischer ULTRACUT FBS II is the perfect powerful concrete screw for top installation comfort.



Width: 220 mm

Length: 1100 mm / 2500 mm

Height: 500 mm / 706 mm

FACTS

ART. NO	COMPONENTS	
12000052	Golf	L=1100mm, 1 Beam
12000053	Golf	L=2500mm, 1 Beam
12000054	Golf	L=1100mm, 2 Beam
12000055	Golf	L=2500mm, 2 Beam

Technical Information

- Tested to withstand force of (Joule) 2.500 – 10.000J
- Vehicle weight equivalent (kg) 2.000-5.000 kg
- Vehicle equivalent speed (km/h) 5,7-7,2 km/h
- Equivalent angle of impact 90°
- Deflection zone 250 mm

Material Properties

- Chemical Resistance high - ISO/TR 10358
- Temperature Range -10° up to + 50°
- Recyclability 100%
- Material: Polyethylene



GOLF

MACHINE GUARD
WAREHOUSE PARTITIONING
AUTOMATED WAREHOUSE


Other

- Color: Yellow (like RAL 1018 traffic yellow) / black
- Indoor use: Yes
- Outdoor use: Yes
- Boreholes: 8
- Fixing: The fixing material is included.
- Fixing dimensions: M12X80 mm

COMBINE WITH



ALFA



MIKE

IMAGES

