

DELTA 3 BEAM

The TÜV-tested and flexible d-flexx safety barrier Delta is an innovative and economic separation of pedestrian areas and trails. Due to the modular system a customized solution can always be supplied by means of individual cuttings. The mounting material is always included in the scope of delivery of the d-flexx Safety Barrier Delta. The fischer ULTRACUT FBS II is the perfect powerful concrete screw for top installation comfort.

Width: 110 mm

Length: Customized Lengths

Height: 1200 mm



FACTS

ART. NO	COMPONENTS	
12000005	Delta End post	3 Beams
12000006	Delta Middle post	3 Beams
12000007	Delta Corner post	3 Beams
12000008	Delta T-post	3 Beams
12000009	Delta Cross post	3 Beams
12000010	Delta Standard beam	3 Beams, L=1500mm
12000011	Delta Individual beam	3 Beams, L=200-1499mm

Technical Information

- Tested to withstand force of (Joule) 2.500J
- Vehicle weight equivalent (kg) 2.000 kg
- Vehicle equivalent speed (km/h) 5,7 km/h
- Equivalent angle of impact 90°
- Deflection zone 250 mm

Material Properties

- Chemical Resistance high - ISO/TR 10358
- Temperature Range -10° up to + 50°



DELTA 3 BEAM


MACHINE GUARD
WAREHOUSE PARTITIONING
AUTOMATED WAREHOUSE

- Recyclability 100%
- Material: Polyethylene

Other

- Color: Yellow (like RAL 1018 traffic yellow) / black
- Indoor use: Yes
- Outdoor use: Yes
- Boreholes: 4
- Fixing: The fixing material is included.
- Fixing dimensions: M10X70 mm

COMBINE WITH



CHARLIE




ECHO



JULIET



DELTA 4 BEAM



DELTA COLUMN