

## **DELTA 4 BEAM**

The TÜV-tested and flexible d-flexx safety barrier Delta is an innovative and economic separation of pedestrian areas and trails. Additionally to the 3 beams Delta safety barrier we now offer you two variants of the Delta barrier with 4 beams. The Delta barrier in 1200 mm height with four beams offers a protection with a difference of only 329 mm to the ground for more protection Due to the modular system a customized solution can always be supplied by means of individual cuttings. The mounting material is always included in the scope of delivery of the d-flexx Safety Barrier Delta. The fischer ULTRACUT FBS II is the perfect powerful contrete screw for top installation comfort.



Width: 110 mm

Length: Customized Lengths

Height: 1200 mm

# **FACTS**

ART. NO	COMPONENTS
12000018	Delta Bollard 4 Beams
12000019	Delta End post 4 Beams
12000020	Delta Cross post 4 Beams
12000021	Delta Middle post 4 Beams
12000022	Delta T-post 4 Beams
12000023	Delta Corner post 4 Beams
12000024	Delta End post 4 Beams, H=1600mm
12000025	Delta Cross post 4 Beams, H=1600mm
12000026	Delta Middle post 4 Beams, H=1600mm
12000027	Delta T-post 4 Beams, H=1600mm
12000028	Delta Corner post 4 Beams, H=1600mm
12000029	Delta Standard beam 4 Beams, L=1500mm
12000030	Delta Individual beam 4 Beams, L=200-1499mm



### **Technical Information**

- Tested to withstand force of (Joule) 2.500J
- Vehicle weight equivalent (kg) 2.000 kg
- Vehicle equivalent speed (km/h) 5,7 km/h
- Equivalent angle of impact 90°
- Deflection zone 250 mm

### **Material Properties**

- Chemical Resistance high ISO/TR 10358
- Temperature Range -40° up to + 50°
- Recyclability 100%
- Material: Polyethylene

#### Other

- Color: Yellow (like RAL 1018 traffic yellow) / black
- Indoor use: Yes • Outdoor use: Yes
- Boreholes: 4
- Fixing: The fixing material is included.
- Fixing dimensions: M10X70 mm



# **COMBINE WITH**











CHARLIE

ECHO

DELTA 3 BEAM

JULIET