

BRAVO

The TÜV-tested and flexible d-flex bollards Bravo absorbs the impact energy. The processed special material does not damage the bollard and the vehicle. Due to its robustness and high visibility the bollard is ideal to be installed on parkings, entrances and for separation of pedestrians areas.

The fixing material is always included in the delivery of d-flexx Bollard Bravi. The fischer ULTRACUT FBS II is the perfect powerful concrete screw for top installation comfort.

Diameter: 200 mm

Height: 516 mm / 760 mm /1200 mm



FACTS

ART. NO	COMPONENTS	
12000048	Bravo H=500mm	Ø 200mm
12000049	Bravo H=750mm	Ø 200mm
12000050	Bravo H=1200mm	Ø 200mm
12000051	Bravo H=1200mm	Ø 200mm, Moveable cuff

Technical Information

- Tested to withstand force of (Joule) 2.000J
- Vehicle weight equivalent (kg) 2.000 kg
- Vehicle equivalent speed (km/h) 5,1 km/h
- Equivalent angle of impact 90°
- Deflection zone 250 mm

Material Properties

- Chemical Resistance high - ISO/TR 10358
- Temperature Range -10° up to + 50°
- Recyclability 100%
- Material: Polyethylene

Other



BRAVO


MACHINE GUARD
WAREHOUSE PARTITIONING
AUTOMATED WAREHOUSE

- Colour: Yellow (like RAL 1018 traffic yellow) / black
- Indoor use: Yes
- Outdoor use: Yes
- Boreholes: 4
- Fixing: The fixing material is included.
- Fixing dimensions: M10X80 mm

COMBINE WITH



JULIET



DELTA COLUMN



DELTA 3 BEAM



NOVEMBER



DELTA 4 BEAM