

FlexGuard Anchor





The FlexGuard Anchor is designed to protect walls, AGV areas, front of racks and other critical structures at ground level from vehicle forks.


Constructed from durable, impact-resistant Polypropylene (PP), it offers reliable protection against accidental impacts from forklifts, pallet trucks, and other industrial vehicles.

Technical Information

AC190	
Size	190mm*130mm
Length	2000mm
Fixing	Chemical Bolt
Impact Energy	Impact test angle at 90°: 5800J, 3.0t forklift hit at 7.0km/h



AC110	
Size	110mm*110mm
Length	2000mm
Fixing	Chemical Bolt
Impact Energy	Impact test angle at 90°: 5800J, 3.0t forklift hit at 7.0km/h



Color RAL 1003 Signal Yellow

Temperature -5 to 50 °C

Application:

Used to protect the front of racks and machinery, electric boxes, walls, corners, and building facades.



FlexGuard

Designed for simple installation, long-lasting performance, and maximum damage prevention.

FlexGuard is a new line of flexible impact barriers designed for flexible impact protection, maximum performance and maximum safety. Constructed from durable, impact-resistant Polypropylene (PP), the FlexGuard product line is highly durable and suitable for use in various industrial environments. Minimizes damage to concrete floors that is typically associated with steel barriers. Its design allows easy installation and maintenance, ensuring minimal downtime for your operations.

Certifications:

Product:

TÜV SÜD TÜV Rhein Test CE ISO RoHS

Material (Armorflex):

Flame Retardant Test



Material:

The material used in FlexGuard, Armorflex, has self-recovery and memory capability. Through special nano processing technology, the molecular structure of the material is constructed into a regular linear network structure. It can absorb, delay and eliminate impact energy and rebound to its original shape after strong impact.

