

## Knob & Handle with integrated Switch

The Safe Escape Lock can be fitted with a proximity switch inside, making sure the power is cut when entering through the door. The knob and euro cylinder lock ensures a locked door from the outside, that only authorized staff with a key can enter. The red handle for panic escape can only be reached from the inside, protected by a black plate from the outside.

The strong locking tube made of aluminum is provided with a fixing where a padlock can be put to secure the door, preventing it from being closed during maintenance operations.

Choose from a variety of switches to be fitted to your lock and our profile euro cylinder, or contact your local locksmith for easy maintenance solutions.



### FACTS

#### Dimensions (approx.)

##### W x H x D

85 mm x 270 mm x 50 mm

The lock is available in two versions; without deadbolt or with a deadbolt with anti-panic function, meaning that the door can be opened from the inside even when it's locked.

The Safe Escape Lock can be supplied pre-mounted on our single hinged doors, or supplied as a kit for easy mounting on site on our single or double hinged doors.

Safe Escape Lock without dead bolt:

- hinged door - Kit 5870
- double hinged door - Kit 5890

Safe Escape Lock with dead bolt:

- hinged door - Kit 5860
- double hinged door - Kit 5880

5870,5890



5860,5880



### SAFETY SWITCHES

Schmersal RSS260-D-ST/RST260-1

Pilz PSEN cs3.1

ABB/Jokab Eva/Adam

Telemecanique XCSR30M12

Euchner CES

