

Test report summary

Smart Fix Door 1000 joules
with Safe Lock

Report No. TR-14-015

Date: 2014-12-11

Place: Troax Test Center

Purpose

To document the effect of an energy impact test from inside the hazard zone with a Smart Fix hinged door, the 60x40 post and the ST30 mesh panels and equipped with a Troax Safe Lock (without switch).

Test material

Panel: ST30 2050x1000

Post: Standard post 60x40

Fixing: Smart Fix hinge

Door lock: Safe Lock

Floor fixing: Bolted to the test rig

Test procedure

The test was performed in accordance with the pendulum test method stated in ISO 14120:2015 Annex C. Panels and posts were assembled with the Smart Fix system and fastened to the test rig with M10 bolts. The pendulum of 100 kg was adjusted so the impact hit the panel at 1466 mm above the floor, i.e. 1316 mm from the bottom of the panel (with a 150 mm floor gap). To reach the energy of 1000 J the 100 kg pendulum was raised 1018 mm from the starting point.

Impact energy

Pendulum mass: 100 kg

Pendulum speed: 16 km/h

$$E = \frac{mv^2}{2} = \frac{100 * (\frac{16}{3,6})^2}{2} = 987,6 J$$

$$E = mgh = 100 * 9,82 * 1.018 = 1000 J$$

Results

The Smart Fix door and the lock withstands the high energy impact. The door panel and the posts absorb all energy and obtain a remaining deformation. The deflection of the door panel was approximately 270 mm in the upper corner and 171 mm in the centre. Despite the high energy impact there was no penetration and no parts departed.



Ola Eriksson
R&D Manager Troax AB



Josephine Granell
Product Manager A&R

Adress / Address

Troax AB
Box 89
SE-330 33 Hillerstorp
Sweden

Telefon / Telephone

+46 (0)370 828 00
Fax
+46 (0)370 824 86

Org.nr / Reg.No.

556093-5719

Hemsida / Website

www.troax.com
E-mail
info@troax.com