

DOUBLE RAIL SLIDING DOOR

The double rail sliding door offers a sliding door that can be opened from two directions. The door can be built from our mesh, polycarbonate, or steel sheet panels to fit your chosen machine guard system. Use the standard panel height 2,050 mm in up to 6 widths. You can also combine the standard panels or order special width panels to create the required door blade size.

The sliding doors are supplied with posts, panels, and door kit for assembly on site.

The door is built with an aluminum rail at the top where the runners move the door blade panels in separate tracks. Guide rails at the bottom keep the door blades in their position, making the sliding doors very stable.

Depending on the risk assessment, you choose the preferred lock for your door; magnetic, Euro cylinder, Safe Lock or any other type of handle solution with or without a safety switch included.


The standard opening width is approximately 700-1,500 mm.




FACTS

ART. NO	COMPONENTS
36905540	Kit 5540 Sliding door dbl rail no lock
36905570	Kit 5570 Sliding door dbl.rail no lock ES
36908290	Kit 8290 Sliding door dbl rail 80x80


ACCESSORIES




SAFE LOCK PLD




SAFE LOCK PLE



SAFE LOCK PLD GL



BRACKETS FOR
VARIOUS SWITCHES



SAFE LOCK PLE GL


COMBINE WITH



POST 60X40




POST 80X80



PANEL ST20



PANEL ST30



PANEL FULL STEEL



DOUBLE RAIL SLIDING DOOR

MACHINE GUARD

IMAGES

