

PANEL ST PC

The polycarbonate ST PC panel is suitable for applications where you need full visibility. Polycarbonate is a naturally transparent thermoplastic. It is both a heat resistant and flame retardant material with excellent fire performance which makes it a good option for machine guarding environments.

The 3 mm polycarbonate sheets are fixed to the panel frame from the inside with screws, making it very strong and impact resistant. The ST PC panel is tested to withstand an impact of 1600 joules together with our Smart Fix system.

Standard panels are available in 8 widths, from 200 mm to 1500 mm to fit a system height of 2200 mm. Standard colour for the panel frame is black RAL 9005, and the panels can be supplied in any colour of your choice.



FACTS

ART. NO	COMPONENTS	HEIGHT (mm)	WIDTH (mm)	MESH SIZE (mm)	FRAME (mm)
31020606	Panel ST PC 2050x200 3mm	2050	200	Polycarbonate	30x20
31030606	Panel ST PC 2050x300 3mm	2050	300	Polycarbonate	30x20
31050606	Panel ST PC 2050x500 3mm	2050	500	Polycarbonate	30x20
31070606	Panel ST PC 2050x700 3mm	2050	700	Polycarbonate	30x20
31080606	Panel ST PC 2050x800 3mm	2050	800	Polycarbonate	30x20
31100606	Panel ST PC 2050x1000 3mm	2050	1000	Polycarbonate	30x20
31120606	Panel ST PC 2050x1200 3mm	2050	1200	Polycarbonate	30x20
31150606	Panel ST PC 2050x1500 3mm	2050	1500	Polycarbonate	30x20


Finish on panels, posts and powder coated accessories has the last figure variants in **ART. NO.**

"1" = RAL 7037 Dusty Grey; "2" RAL 1018 Zink Yellow; "5" All other RAL colours or cut/welded; "6" RAL 9005 Jet Black, "8" Hot dip galvanized

ACCESSORIES



CUTTING PROFILES
PC



KICKPLATE



SNAPPER



GAP COVER



FOAM INFILL

COMBINE WITH



POST 60X40



SMART FIX



SAFE FIX

IMAGES

