

CHARLIE

The TÜV-tested and flexible d-flexx Traffic Barrier Charlie provides an optimal protection for machines, inventory and employees. Thanks to the easy and fast assembly in combination with individually cutted lengths, traffic routes can be separated quickly and easily from work areas or pedestrian paths. Bollards are a useful addition at the end of the traffic barriers. The fixing material is always included in the delivery. The fischer ULTRACUT FBS II is the perfect powerful concrete screw for top installation comfort.



Length: Customized lengths

Height: 516 mm

FACTS

ART. NO	COMPONENTS
12000001	Charlie End post
12000002	Charlie Middle post
12000003	Charlie Standard beam Ø 160mm, L=930mm
12000004	Charlie Individual beam ∅ 160mm, L=400-929mm


Technical Information

- Tested to withstand force of (Joule) 10.000 J
- Vehicle weight equivalent (kg) 5.000 kg
- Vehicle equivalent speed (km/h) 7,2 km/h
- Equivalent angle of impact 90°
- Deflection zone 250 mm

Material Properties

- Chemical Resistance high ISO/TR 10358
- Temperature Range -40° up to + 50°
- Recyclability 100%
- Material: Polyethylene

Other





• Color: Yellow (like RAL 1018 traffic yellow) / black

• Indoor use: Yes • Outdoor use: Yes

• Boreholes: 4

• Fixing The fixing material is included. The Fischer ULTRACUT FBS II is the perfect powerful concrete screw for top installation comfort.

• Fixing dimensions: M12X80 mm



COMBINE WITH







JULIET





MIKE

ECHO

DELTA 4 BEAM

DELTA 3 BEAM



IMAGES

